



PRODUCT INFO:

PUSH TUBE SAMPLER S

Item code PT**C,** The Push-Tube samplers are for taking undisturbed samples in normal soils. The thin walled tubes are held onto a stepped spigot on a Drive Adaptor by 2 or 4 cap screws. The Drive Adaptor enables the tube to be attached to an Extension Rod and/or Slide Hammer. The tubes come in various lengths upto 300mm long and in nominal sizes of 50mm or 62mm or 75mm diameters. The tubes are available in unpainted steel or stainless steel (add 45% to the price of steel tubes for the stainless steel ones). An allen key is supplied to undo the cap screws. The tubes are drilled with 4 holes and have 4 screws but 2 are enough to hold them on and the other 2 holes just make it easier to fit and the 2 extra screws become spares. The cutting end of the tubes is sharpened and is rolled in our lathe to slightly reduce the cutting diameter which reduces friction between the soil and inside of the tube.

Options: Various lengths, diameter and steel or stainless steel.

Drive Adaptors are coarse thread only; Needs Slide Hammer and Extension Rod to operate.

PUSH TUBE SAMPLER - steel or stainless steel		Kgs	Price	GST	Total
PT5002C	50mm x 200mm steel tube, sharpened	0.5			
PT6302C	63mm x 200mm steel tube, sharpened	0.7			
PT7502C	75mm x 200mm steel tube, sharpened	0.9			
PTADAPT (size) C	Drive adaptor to suit size and connection.	1.2			
<i>Note: Other lengths available. Stainless Steel also available, add 45% to price. Plastic end caps also available.</i>					

NOTE: See current price list.



**62mm x 230mm stainless steel push tube (1.6mm wall tickness).
Showing stainless steel drive adaptor (included) and optional plastic end caps.
Comes with 4 x stainless steel allen headed screws and an allen key**